

BestPack

the total tape sealing solution

CSX Series

Fully Automatic Random Side Drive

The BestPack™ CSX Series Fully Automatic Random Carton Sealer's advanced engineering provides the high speed output, and are built for rugged dependability. The CSX design uses three independent operating stations that include the Indexer, Folding Area, and Sealing Area. For operational dependability and performance, maintenance free oil-less air cylinders are used. These features along with others in our CSX Series set BestPack apart from others in the marketplace. These sealers are designed to meet all your operator free random carton sealing applications.

All systems incorporate our exclusive 2" or 3" pop out pressure sensitive "High Speed" tape heads with patented tab adjustment. All BestPack units are available in our standard baked enamel finish or food grade 304 stainless steel. Custom sizes available for your application.



Key Points of the Carton Sealer



Does Not Require Operator



Random Cartons



Top & Bottom Seal

Features

- Handles Random Carton Sizes
- Adjustable Bed Height from 24.25" to 29.5"
- Independent 3-Stage Operation: Indexing, Flap-Folding, & Sealing
- In-Line Carton Closure
- Reduced Cycle Time
- Rugged Construction
- Operator Free Design
- Cost Effective
- Height Sensors
- Tape Roll Lengths: 1000 yd., 1500 yd., & 2000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Rugged Construction

- Indexer with Carton Centering Device
- Automatic Flap-Fold
- Upper Side Compression
- Sensors Handles Empty/Overfilled Cartons
- "Low Tape" Warning Light
- Heavy Duty Frame and Locking Casters
- Interlock Safety Gates

Options

- Stainless Steel
- No Tape Sensor
- No Flap Sensor
- Retractable Top or Bottom Tape Heads
- Touch Screen Human Interface
- User Specified PLC Brand
- Higher than 125ft/min belt speed
- Infeed/Exit Conveyor

Distributed by CBM Systems, Inc.

+1 (909) 670-8888 | sales@cbmsystem.com | www.cbmsystem.com

© 2016 BestPack Packaging Systems. All rights reserved.



Extra Accessories to Improve Efficiency



Spare Parts Kit



Infeed/Exit Conveyor
w/L-Bracket Holder/Stopper



Spare Tape Head



Carton Sealing Tape

- Stainless Steel
- High Speed Motor Upgrade (Up to 125 ft./mm.)
- Motorized Height and/or Width Adjustment

Machine & Carton Specifications

110 Volts 60 Hz
Power Requirements

Up to 12 Cartons/min.
Speed

100 PSI
12+ CFM
Air Requirements

1320 lbs
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
CSX22-2 2" Tape Head	(95.8") x (40.0") x (90.5")	(9.0" - 25.0") x (6.3" - 20.5") x (5.5" - 22.0")	Conveyor Height Varies	Up to 12	1320
CSX22-3 3" Tape Head	(95.8") x (40.0") x (90.5")	(9.0" - 25.0") x (6.3" - 20.5") x (5.5" - 22.0")	Conveyor Height Varies	Up to 12	1320

Information subject to change without notice.
© 2016 BestPack Packaging Systems. All rights reserved.



CBM Systems, Inc.
1599 Monte Vista Avenue
Claremont, CA 91711
sales@cbmsystem.com
(909) 670-8888
www.cbmsystem.com

