

RS Series

Random Sidedrive

The BestPack® RS Series Semi-Automatic Random Tape Carton Sealers are built for speed and rugged dependability. With these systems, random sized cartons are handled with ease whether your application needs call for a low profile top & bottom sealer or a heavy duty work horse.

All systems incorporate our exclusive pop out pressure sensitive "High Speed" tape heads with patented tab adjustment available in both 2" or 3".



Key Points of the Carton Sealer



Operator Fed



Random Cartons



Top & Bottom Seal

Features

- Handles Random Carton Sizes
- Adjustable Bed Height from RS22 & RS23: 20.5" - 30"
RS33: 20.5" - 30"
- 2 Side Belt Driven
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- Tape Roll Lengths: 1000 yd., 1500 yd., 2000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Rugged Construction
- Capable of Interchanging 2" or 3" Tape Heads
- Electrical on/off box can be mounted on either side of the carton sealer
- Exclusive Pop-out pressure sensitive "high speed" tape head with patented tab adjustment and noise reduction arm

Options

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft.)
- Locking Heavy-Duty Casters
- Interlock Safety Gates
- Low or No Tape Sensor
- Infeed/Exit Conveyor w/Stabilizer
- Stainless Steel

Extra Accessories to Improve Efficiency



Spare Parts Kit



Locking Casters



Long Infeed/Exit Conveyor
w/ L-Bracket



Spare Tape Head

- High Speed Motor Upgrade (Up to 125 ft.)
- Carton Sealing Tape

Machine & Carton Specifications

110 Volts 60 Hz
Power Requirements

Up to 15 Cartons/min.
Speed
(2" Carton Sealer)

80 PSI
5 CFM
Air Requirements

410-600 lbs
Shipping Weight

| Model | Machine Dimensions Length x Width x Height | Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.) | Conveyor Height Adjustment Height (min. - max.) | Cartons per min. | Shipping Weight (lbs.) |
|-------------------------------|---|--|--|------------------|------------------------|
| RS22-2 2" Tape Head | (42.9") x (34.8") x (71.8") | (6.0" - U) x (4.25" - 20") x (4" - 21") | (20.5" - 30") | Up to 15 | 410 |
| RS22-3 3" Tape Head | (42.9") x (34.8") x (71.8") | (6.0" - U) x (5.25" - 21") x (4" - 21") | (20.5" - 30") | Up to 15 | 410 |
| RS23-2 2" Tape Head | (42.9") x (34.8") x (76") | (6.0" - U) x (4.5" - 20") x (4" - 30.0") | (20.5" - 30") | Up to 12 | 440 |
| RS23-3 3" Tape Head | (42.9") x (34.8") x (76") | (6.0" - U) x (5.5" - 21") x (4" - 30.0") | (20.5" - 30") | Up to 12 | 440 |
| RS32-2 2" Tape Head | (42.9") x (44.2") x (71.8") | (6.0" - U) x (4.5" - 30") x (4" - 20.5") | (20.5" - 30") | Up to 12 | 462 |
| RS32-3 3" Tape Head | (42.9") x (44.2") x (71.8") | (6.0" - U) x (5.5" - 30") x (4" - 20.5") | (20.5" - 30") | Up to 12 | 462 |
| RS33-3 3" Tape Head | (42.9") x (44.2") x (76") | (6.0" - U) x (5.5" - 30") x (4" - 30.0") | (20.5" - 30") | Up to 12 | 600 |

Information subject to change without notice.
© 2016 BestPack Packaging Systems. All rights reserved.

U - Unlimited
High Speed Option Available



CBM Systems, Inc.
1599 Monte Vista Avenue
Claremont, CA 91711
sales@cbmsystem.com
(909) 670-8888
www.cbmsystem.com

